



OFFICE OF THE PRINCIPAL
HANDIQUE GIRLS' COLLEGE
GUWAHATI - 781001, ASSAM

Ph.: 0361-2970214 (O)

Dr. Ranjit Sarma, M.Sc., M. Phil, Ph.D.
Principal-cum-Secretary

e-mail : hgcollege75@gmail.com
Website: www.hgcollege.edu.in

Ref. No. : HGC/ESTT/NIQ/2024/01/006

Date : 08.07.2024

NOTICE INVITING QUOTATION

Sealed quotation on firm letterhead affixing a non refundable court fee stamp of Rs. 8.25 are hereby invited from the reputed registered firms/contractors of relevant categories having experience of execution of similar nature of constriction/renovation works as mentioned below at Handique Girls' College, Guwahati-01, Assam. The quotations along with GST Registration certificate, PAN Card, Trade License and Experience Certificate of execution of works of similar nature have to be submitted at the designated place at the Office of the undersigned. The sealed envelope must be superscribed with the Quotation Number and addressed to the undersigned. The quotation will be received by the Office of the Principal, Handique Girls' College up to **15th July, 2024, 2.00 pm** and will be opened on the same day at 3.00 pm. Contractor or one authorized person may be present at the time of opening.

1.	Name of Work	Repair & Renovation of Existing Girl's Toilet in the Arts Block (1 st Floor) with State of the Arts Amenities at Handique Girls' College, Guwahati-01, Assam as per DSR 2021
2.	Estimated amount	Rs.5,72,700.00
3.	Time of completion	30 days
4.	Earnest Money to be deposited with the quotation Paper	2 % of Estimated value for General Category and 1% of estimated value for SC/ST/OBC/MOBC Category.
5.	Security Deposit	Addition 3% of Estimated value (only by Successful bidder)

The Earnest and Security amount will have to be deposited by Demand Draft in the favour of Principal-Cum Secretary, Handique Girls' College, Guwahati, Payable at Guwahati. Quotations submitted by the bidders shall remain valid for acceptance for a period of 180 (one hundred eighty) days from the date of opening of such quotations. The bidder/s shall not be entitled to revoke or cancel his/their quotation/s or to vary any of the terms thereof during the said period of validity. The period of liability shall be 12 (Twelve) months reckoned from the date of issue of completion certificate on actual completion of the work. The taxes as per rule will be deducted at source from the total bill value. Quotation not properly sealed will be liable for cancellation.

Principal
Handique Girls' College
Guwahati-01, Assam

Memo No.: HGC/ESTT/NIQ/2024/01/006-A, Dated: 08.07.2024

Copy to:

1. Notice board/Website for display.
2. Convenor, Construction Committee for kind information.
3. Office file for record.

Principal
Handique Girls' College
Guwahati-01, Assam

**MEASUREMENT SHEET FOR REPAIR & RENOVATION OF EXISTING GIRL'S TOILET
IN THE ARTS BLOCK (FIRST FLOOR) WITH STATE OF THE ART AMENITIES AT HANDIQUE GIRL'S
COLLEGE, DIGHALIPUKHURIPAR, PANBAZAR, GUWAHATI AS PER DSR 2021**

SL. NO.	SOR I/No.	Description of Items	NO.	L	B	H	QTY	Unit	Rate	Amount
1	15.3	Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer - in- charge								
		Floor	1	8.4	3.3	0.2	5.54	CUM		
		Lintel	2	8.4	0.15	0.15	0.38	CUM		
		Lintel	3	3.3	0.15	0.15	0.22	CUM		
						Total	6.14	CUM		
2	15.7	Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge.								
		In cement mortar cum								
	15.7.4	Wall Dismatle	1	8.4	1.2	0.15	1.51	CUM		
		Wall Dismatle	1	8.4	3	0.15	3.78	CUM		
		Wall Dismatle	1	3.3	1.2	0.15	0.59	CUM		
		Wall Dismatle	3	3.3	3	0.15	4.46	CUM		
		Wall Dismatle	3	1.4	3	0.15	1.89	CUM		
		Deduct Door	-8	0.8	2.1	0.15	-2.02	CUM		
		Deduct Window	-3	0.75	1.2	0.15	-0.41	CUM		
						Total	9.81	CUM		
3	15.12	Dismantling doors, windows and clerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead :								
	15.12.1	Of area 3 sq. metres and below								
		Door	8				8.00	Each		
		Window	3				3.00	Each		
						Total	11.00	Each		
4	15.23.2	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.								
		For thickness of tiles above 25 mm and up to 40 mm								
		Floor Tile	1	8.4	3.3		27.72	SQM		
5	6.13	Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level.								
	6.13.2	Cement mortar 1:4 (1 cement :4 coarse sand)								
		Wall	1	8.4		1.2	10.08	SQM		
		Wall	1	3.3		1.2	3.96	SQM		
		Partition Wall	1	3.9		2.4	9.36	SQM		
		Partition Wall	2	1.2		2.4	5.76	SQM		
		Wall	1	3.1		3	9.30	SQM		
		Wall	2	2.1		3	12.60	SQM		
		Wall	1	2.9		3	8.70	SQM		
		Deduct Door	-7	0.8		2.1	-11.76	SQM		
		Deduct Window	-7	0.75		1.35	-7.09	SQM		
						Total	40.91	SQM		

SL. NO.	SOR I/No.	Description of Items	NO.	L	B	H	QTY	Unit	Rate	Amount
6	9.119	Providing and fixing factory made P.V.C. door frame of size 50x47 mm with awall thickness of 5 mm, made out of extruded 5mm rigid PVC foam sheet, mitred at corners and joined with 2 Nos of 150 mm long brackets of 15x15 mm M.S. square tube, the vertical door frame profiles to be reinforced with 19x19 mm M.S. square tube of 19 gauge, EPDM rubber gasket weather seal to be provided through out the frame. The door frame to be fixed to the wall using M.S. screws of 65/100 mm size, complete as per manufacturer's specification and direction of Engineerin-Charge.								
		PVC DOOR	7	5			35.00	MTR		
7	9.120.2	Providing and fixing factory made panel PVC door shutter consisting of frame made out of M.S. tubes of 19 gauge thickness and size of 19 mm x 19 mm for styles and 15x15 mm for top & bottom rails. M.S. frame shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be flat and 20 mm shall be tapered in 45 degree on the inner side to form top and bottom rail and 115 mm wide PVC sheet out of which 75 mm shall be flat and 20 mm shall be tapered on both sides to form lock rail. Top, bottom and lock rails shall be provided both side of the panel. 10 mm (5 mm x 2) thick, 20 mm wide cross PVC sheet be provided as gap insert for top rail & bottom rail, paneling of 5 mm thick both side PVC sheet to be fitted in the M.S. frame welded/ sealed to the styles & rails with 7 mm (5 mm+2 mm) thick x 15 mm wide PVC sheet beading on inner side, and joined together with solvent cement adhesive. An additional 5 mm thick PVC strip of 20 mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete as per direction of Engineer-in-charge, manufacturer's specification & drawing. 30 mm thick pre laminated PVC door shutters								
		PVC DOOR	7	0.75	2.1		11.03	SQM		
8	9.97	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete								
	9.97.1	300x10 mm								
		Door					7.00	EACH		
9	9.98	Providing and fixing aluminium pull bolt lock, ISI marked, anodised (anodiccoating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade, with necessary screws bolts, nut and washers etc. complete.								
		Door					7.00	EACH		
10	11.1	Brick on edge flooring with bricks of class designation 7.5 on a bed of 12 mm cement mortar, including filling the joints with same mortar, with common burnt clay non modular bricks:								
		Floor	1	4	1.2		4.80	SQM		

SL. NO.	SOR I/No.	Description of Items	NO.	L	B	H	QTY	Unit	Rate	Amount
11	8.31	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.								
		Wall	1	8.4	2.1	1	17.64	SQM		
		Partition Wall	1	3.9	2.1	2	16.38	SQM		
		Partition Wall	2	1.2	2.1	2	10.08	SQM		
		Wall	1	3.3	2.1	1	6.93	SQM		
		Wall	1	3.3	2.1	2	13.86	SQM		
		Wall	1	2.9	2.1	1	6.09	SQM		
		Wall	1	2	2.1	2	8.40	SQM		
		Wall	2	1.5	2.1	1	6.30	SQM		
		Wall	2	1.2	2.1	1	5.04	SQM		
		Deduct Window	-7	0.75	1.2	1	-6.30	SQM		
		Deduct Window	-2	0.75	2.1	1	-3.15	SQM		
		Deduct Door	-5	0.75	2.1	2	-15.75	SQM		
						Total	65.52	SQM		
12	11.41	Glazed Vitrified tiles Matt/Antiskid finish of size Size of Tile 600 x 600 mm								
		Floor Tiles	1	8.4	3.3		27.72	SQM		
13	5.2	Reinforced cement concrete work in walls (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts etc. above plinth level up to floor five level, excluding cost of centering, shuttering, finishing and reinforcement :								
		1:1.5:3 (1 cement : 1.5 coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources)								
	5.2.2	Mulion Post	14	3.2	0.15	0.15	1.01	CUM		
		Linel	2	8.4	0.15	0.15	0.38	CUM		
		Linel	2	3.3	0.15	0.15	0.15	CUM		
		Linel	3	1.2	0.15	0.15	0.08	CUM		
		Linel	2	2.1	0.15	0.15	0.09	CUM		
		Chajjah	7	0.75	0.3	0.075	0.12	CUM		
						Total	1.83	CUM		
14	5.9	FORM WORK								
		Centering and shuttering including strutting, propping etc. and removal of form for								
	5.9.5	Lintels, beams, plinth beams, girders, bressumers and cantilevers								
		Linel	2	8.4	0.15	2	5.04	SQM		
		Linel	2	3.3	0.15	2	1.98	SQM		
		Linel	3	1.2	0.15	2	1.08	SQM		
		Linel	2	2.1	0.15	2	1.26	SQM		
						Total	9.36	SQM		
	5.9.6	Columns, Pillars, Piers, Abutments, Posts and Struts								
		Mulion Post	14	3.2	0.15	4	26.88	SQM		
						Total	26.88	SQM		
	5.9.3	Suspended floors, roofs, landings, balconies and access platform								
		Chajjah	7	0.75	0.3	2	3.15	SQM		

SL. NO.	SOR I/No.	Description of Items	NO.	L	B	H	QTY	Unit	Rate	Amount
15	5.22	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete above plinth level								
		Thermo-Mechanically Treated bars of grade Fe-500D or more.								
		Mulion Post	14	3.2	4	0.89	159.49	KG		
		Stirrup	14	0.5	26	0.39	70.98	KG		
		Linel	2	8.4	4	0.62	41.66	KG		
		Stirrup	2	0.5	68	0.39	26.52	KG		
		Linel	2	3.3	4	0.62	16.37	KG		
		Stirrup	2	0.5	27	0.39	10.53	KG		
		Linel	3	1.2	4	0.62	8.93	KG		
		Stirrup	3	0.5	10	0.39	5.85	KG		
		Linel	2	2.1	4	0.62	10.42	KG		
		Stirrup	2	0.5	17	0.39	6.63	KG		
		Chajjah	7	0.75	3	0.62	9.77	KG		
		Chajjah	7	0.3	6	0.62	7.81	KG		
						Total	374.95	KG		
16	13.4	12 mm cement plaster of mix :								
	13.4.1	1:4 (1 cement: 4 coarse sand)								
		Exterior Wall	1	8.4	1	3.3	27.72	SQM		
		Exterior Wall	1	3.3	1	3.3	10.89	SQM		
		Chajjah	7	0.75	2	0.3	3.15	SQM		
		Deduct Window	-7	0.75	1.35	1	-7.09	SQM		
		Wall	1	8.4	1.1	1	9.24	SQM		
		Partition Wall	1	3.9	0.3	2	2.34	SQM		
		Partition Wall	2	1.2	0.3	2	1.44	SQM		
		Wall	1	3.3	1.1	1	3.63	SQM		
		Wall	1	3.3	1.1	2	7.26	SQM		
		Wall	1	2.9	1.1	1	3.19	SQM		
		Wall	1	2	1.1	2	4.40	SQM		
		Wall	2	1.5	1.1	1	3.30	SQM		
		Wall	2	1.2	1.1	1	2.64	SQM		
		Deduct Window	-7	0.75	1.2	1	-6.30	SQM		
		Deduct Door	-2	0.75	2.1	2	-6.30	SQM		
		Deduct Door	-5	0.75	2.1	2	-15.75	SQM		
		Wall	1	4.5	3.2	1	14.40	SQM		
		Wall	1	1.5	3.2	1	4.80	SQM		
						Total	62.96	SQM		
17	13.26	Providing and applying plaster of paris putty of 2 mm thickness overplastered surface to prepare the surface even and smooth complete								
		Exterior Wall	1	8.4	1	3.3	27.72	SQM		
		Exterior Wall	1	3.3	1	3.3	10.89	SQM		
		Chajjah	7	0.75	2	0.3	3.15	SQM		
		Deduct Window	-7	0.75	1.35	1	-7.09	SQM		
		Wall	1	8.4	1.1	1	9.24	SQM		
		Partition Wall	1	3.9	0.3	2	2.34	SQM		
		Partition Wall	2	1.2	0.3	2	1.44	SQM		
		Wall	1	3.3	1.1	1	3.63	SQM		
		Wall	1	3.3	1.1	2	7.26	SQM		

SL. NO.	SOR I/No.	Description of Items	NO.	L	B	H	QTY	Unit	Rate	Amount
		Wall	1	2.9	1.1	1	3.19	SQM		
		Wall	1	2	1.1	2	4.40	SQM		
		Wall	2	1.5	1.1	1	3.30	SQM		
		Wall	2	1.2	1.1	1	2.64	SQM		
		Deduct Window	-7	0.75	1.2	1	-6.30	SQM		
		Deduct Door	-2	0.75	2.1	2	-6.30	SQM		
		Deduct Door	-5	0.75	2.1	2	-15.75	SQM		
		Wall	1	4.5	3.2	1	14.40	SQM		
		Wall	1	1.5	3.2	1	4.80	SQM		
		Total					62.96	SQM		
18	13.41	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade								
	13.41.1	New work (two or more coats) over and including water thinnable priming coat with cement primer								
		Wall	1	8.4	1.1	1	9.24	SQM		
		Partition Wall	1	3.9	0.3	2	2.34	SQM		
		Partition Wall	2	1.2	0.3	2	1.44	SQM		
		Wall	1	3.3	1.1	1	3.63	SQM		
		Wall	1	3.3	1.1	2	7.26	SQM		
		Wall	1	2.9	1.1	1	3.19	SQM		
		Wall	1	2	1.1	2	4.40	SQM		
		Wall	2	1.5	1.1	1	3.30	SQM		
		Wall	2	1.2	1.1	1	2.64	SQM		
		Deduct Window	-7	0.75	1.2	1	-6.30	SQM		
		Deduct Door	-2	0.75	2.1	2	-6.30	SQM		
		Deduct Door	-5	0.75	2.1	2	-15.75	SQM		
		Wall	1	4.5	3.2	1	14.40	SQM		
		Wall	1	1.5	3.2	1	4.80	SQM		
		Total					28.29	SQM		
19	13.48	Finishing walls with 100% Premium acrylic emulsion paint having VOC less than 50 gm/litre and UV resistance as per IS 15489:2004, Alkali & fungal resistance, dirt resistance exterior paint of required shade (Company Depot Tinted) with silicon additives								
		New work (Two or more coats applied @ 1.43 litre/ 10 sqm. Over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm.								
		Exterior Wall	1	8.4	1	3.3	27.72	SQM		
		Exterior Wall	1	3.3	1	3.3	10.89	SQM		
		Chajjah	7	0.75	2	0.3	3.15	SQM		
		Deduct Window	-7	0.75	1.35	1	-7.09	SQM		
		Total					34.67	SQM		
20	21.3.2	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gaske etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item):								
		With float glass panes of 5 mm thickness (weight not less than 12.50 kg/sqm)								
		Window	7	0.75		1.35	7.09	SQM		

Grand Total-

**DETAILS ESTIMATE FOR SANITARY & WATER SUPPLY -TOILET OF ZOOLOGY DEPARTMENT AT
HANDIQUE GIRL'S COLLEGE, DIGHALIPUKHURIPAR, PANBAZAR, GUWAHATI AS PER CPWD DSR 2021**

Sl. No.	Item No.	Description of Item	Qty	Units	Rate	Amount
1	17.1	Providing and fixing water closet squatting pan (Indian type W.C. pan) with 100 mm sand cast Iron P or S trap, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required:				
	17.1.1	White Vitreous china Orissa pattern W.C. pan of size 580x440 mm with integral type foot rests	3.00	Each		
2	17.2	Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required :				
	17.2.1	W.C. pan with ISI marked white solid plastic seat and lid	2.00	EACH		
3	17.7	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require:				
	17.7.1	White Vitreous China Wash basin size 630x450 mm with a pair of 15 mm C.P. brass pillar taps	5.00	Each		
4	17.60.1	Providing and fixing trap of self cleansing design with screwed down or hinged grating with or without vent arm complete, including cost of cutting and making good the walls and floors :				
		100 mm inlet and 100 mm outlet				
		Sand cast iron S&S as per IS: 3989	5.00	Each		
5	17.32	Providing and fixing mirror of superior glass (of approved quality) and of required shape and size with plastic moulded frame of approved make and shade with 6 mm thick hard board backing : 17.32.1 Circular shape 450 mm dia	5	Each		
6	17.7	Providing and fixing PTMT Bottle Trap for Wash basin and sink. 17.70.1 Bottle trap 31mm single piece moulded with height of 270 mm, effective length of tail pipe 260 mm from the centre of the waste coupling, 77 mm breadth with 25 mm minimum water seal, weighing not less than 260 gms	5	Each		
	17.69	Providing and fixing PTMT Waste Coupling for wash basin and sink, of approved quality and colour. 17.69.1 Waste coupling 31 mm dia of 79 mm length and 62mm breadth weighing not less than 45 gms	10	Each		
7	17.36	Providing and fixing soil, waste and vent pipes : 17.35.1 100 mm dia 17.35.1.1 Sand cast iron S&S pipe as per IS: 1729	12	R.m		
		75 mm diameter : 17.35.2.1 Sand cast iron S&S pipe as per IS: 1729	12	R.m		

Sl. No.	Item No.	Description of Item	Qty	Units	Rate	Amount
8	17.38	Providing and fixing bend of required degree with access door, insertion rubber washer 3 mm thick, bolts and nuts complete. 17.38.1 100 mm dia 17.38.1.1 Sand cast iron S&S as per IS - 1729	5	Each		
		75 mm dia 17.38.2.1 Sand cast iron S&S as per IS - 1729	5	Each		
9	1.39	Providing fitting and fixing 110mm dia. PVC cowl with ISI make complete as directed and specified.	2	Each		
10	18.9	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings This includes jointing of pipes & fittings with one step CPVC solvent cement, trenching, refilling & testing of joints complete as per direction of Engineer in Charge.				
		18.9.4 32 mm nominal dia Pipes	15	RM		
11	18.8	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc. 18.8.1 15 mm nominal dia Pipes	12	RM		
		18.8.2 20 mm nominal dia Pipes	13	RM		
		18.8.3 25 mm nominal dia Pipes	10	RM		
12	18.5	Providing and fixing C.P. brass long nose bib cock of approved quality conforming to IS standards and weighing not less than 810 gms. 18.50.1 15 mm nominal bore	10	Each		
	18.52	Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931.	2	Each		
13	18.17	Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end) : 18.17.1 25 mm nominal bore	2	Each		
		18.17.3 40 mm nominal bore	2	Each		
14	18.90.4	Providing and fixing required Stainless Steel Fitting of press fit design of grade AISI 304 conforming to JWWA G116 standard with V-profile or M-profile and with O-ring sealing gasket of EPDM material of required dia as per direction of Engineer-in-charge.				
		Elbow 90° For 34.00 mm outer dia pipe each	10	Each		
15	17.71	Providing and fixing PTMT liquid soap container 109 mm wide, 125 mm high and 112 mm distance from wall of standard shape with bracket of the same materials with snap fittings of approved quality and colour, weighing not less than 105 gms	10	Each		

Grand Total-

MEASUREMENT SHEET FOR ELECTRICAL WORKS FOR THE REPAIR & RENOVATION OF THE GIRL'S TOILET IN THE ARTS BLOCK (FIRST FLOOR) WITH STATE OF THE ART AMENITIES. AT HANDIQUE GIRL'S COLLEGE, DIGHALIPUKHURIPAR, PANBAZAR, GUWAHATI

Sl No	Item No	Item	Qty	Unit	Rate	Amount
1	1.3	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface/ recessed medium class PVC conduit, with modular switch, modular plate, suitable GI box and earthing the point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc as required.				
	1.3.2	Group B	10	Each		
	1.3.3	Group C	12	Each		
2	1.7	Wiring for circuit/ submain wiring along with earth wire with the following sizes of FRLS PVC insulated copper conductor, single core cable in surface/ recessed medium class PVC conduit as required				
	1.7.1	2 X 1.5 sq. mm + 1 X 1.5 sq. mm earth wire	60	m		
	1.7.2	2 X 2.5 sq. mm + 1 X 2.5 sq. mm earth wire	20	m		
3	1.27	Supplying and fixing following size/ modules, GI box along with modular base & cover plate for modular switches in recess etc as required.				
	1.27.1	1 or 2 Module (75mmX75mm)	6	Each		
	1.27.2	3 Module (100mmX75mm)	2	Each		
4	2.10	Supplying and fixing 5 amps to 32 amps rating, 240/415 volts, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required.				
	2.10.2	Single Pole and Neutral	2	Each		
5	1.50	Installation of exhaust fan in the existing opening, including making good the damage, connection, testing, commissioning etc. as required.				
	1.50.1	Upto 450 mm sweep	6	Each		
6	As per approved rate analysis	Supply with fitting, fixing of 12 Watt LED Bulb 3 star range (BAJAJ/POLYCAB/PHILIPS/EQUIVALENT)	8	Each		
7	As per approved rate analysis	Supply with fitting, fixing of LED Tubelight 20Watt (BAJAJ/POLYCAB/PHILIPS/EQUIVALENT)	2	Each		
Total-						